

1D \ 2D



# I2

## Industrial 2D Barcode Scanner

### • Excellent Identification Ability

High performance scanning module, easily decode all common 1D and 2D symbologies

### • Long Service Life

Scan button with over 30 million times operation, and adopted ultra low power consumption.

### • Convenient and Comfortable Operation

Fashionable and ergonomics design, boost work efficiency and convenient for long hours of usage.

### • High Quality

Adopt high quality wires and inflaming retarding materials with the international standard, recyclable and practical shell to protect the device.


### • Industrial Grade Durability

IP54 industrial grade, and bear the height of 1.8m dropping and ground impact.


### Healthcare



### Logistics



### Manufacturing



### Retailing



I2 is an industrial grade 2D optical image scanner. It delivers industrial leading performance and durability in Retail, logistics, Manufacturing, Medical store, Warehouse and other fields of applications.

## TECHNICAL SPECIFICATIONS

### Performance Parameters

Light source	Visible red light emitting diodes (610-640nm) for aiming
Image sensor	CMOS. Resolution: 1280x1024 pixels
Decode capability	1D: UPC/EAN, UPC/EAN with supplements, ISBN/ISSN, UCC, Code 128, Code 39, Code 39 (Full ASCII), code 32, Interleaved 2 of 5, Matrix 2 of 5, Discrete 2 of 5, Codabar, MSI/Plessey, Chinese 2 of 5, China Postal Code, GS1 DataBar, etc. 2D: PDF417, Data Matrix, QR, Aztec, Maxicode, etc.
Scan Angle	±360°, ±60°, ±60° (Roll, Skew, Pitch)
Scan precision	≥3mil
Print contrast	20%
Prompt mode	Buzzer, LED indicator light
Interface	USB, USB-COM
Trigger mode	Manual, Continuous automatic scan and auto sensing scanning (optional)
Setting method	Scan configuration barcode
Current and voltage	35mA (standby), 260mA (working), 5 VDC ±10%

### Physical Parameters

Over dimension	L X W X H (153.2x66x110.5mm)
Weight	310g
Material	ABS+PC environmentally friendly materials

### Environmental Parameters

Working temperature	-20°C to 50°C
Storage temperature	-40°C to 60°C
Anti-drop	Withstand drop from 1.8m to concrete floor
Humidity	5% to 95% RH
IP grade	IP54
Circumstance luminance	0-100,000Lux