

1D



# C3-G

## Durable 1D Laser Wireless Scanner

### • Ultra-long Distance Data Transmission

150 meters long distance data transmission, supports automatic frequency modulation and inventory mode.

### • Excellent Identification Ability

High performance scanning module, easily decode all common one-dimension barcode.

### • Powerful Endurance Ability

1200mAh rechargeable polymer lithium battery, make device could continuously work for more than 20 hours with the fully charged.

### • High Quality

Adopt high quality wires and inflaming retarding materials with the international standard, recyclable and practical shell to protect the device.


### • Industrial Grade Durability

IP54 industrial sealing grade, and bear the height of 1.5m dropping and ground impact.


#### Healthcare



#### Logistics



#### Manufacturing



#### Retailing



C3-G with professional high-performance 1D Laser scan engine, and take 2.4GHz wireless technology, with 2.4G data receiver. Easily read printed 1D barcode, It designed for retail, logistics, manufacturing, healthcare , warehouse, etc.

## TECHNICAL SPECIFICATIONS

### Performance Parameters

Light source	Laser
Decoding speed	≥300 times/s
Decode capability	UPC/EAN, UPC/EAN with supplements, ISBN/ISSN, UCC, Code 128, Code 39, Code 39 (Full ASCII), code 32, Interleaved 2 of 5, Matrix 2 of 5, Discrete 2 of 5, Codabar, MSI/Plessey, Chinese 2 of 5, China Postal Code, GS1 DataBar, etc.
Scan Angle	±40°, ±60°, ±60° (Roll, Skew, Pitch)
Scan precision	≥3mil
Print contrast	20%
Prompt mode	Buzzer, LED indicator light
Interface	USB, USB-COM
Trigger mode	Manual, Continuous automatic scanning
Memory	512KB(Save 40,000 barcode data)
Battery	1200mAh (charging time is 4h)
Current and voltage	30mA (standby), 160mA (working), 5 VDC ±10%
Work frequency	2.4GHz
Data communication distance	150m (open area)
Setting method	Scan configuration barcode

### Physical Parameters

Over dimension	L X W X H (175x72x100mm)
Weight	210g
Material	ABS+PC environmentally friendly materials

### Environmental Parameters

Working temperature	-20°C to 50°C
Storage temperature	-40°C to 60°C
Anti-drop	Withstand drop from 1.5 m to concrete floor
Humidity	5% to 95% RH
IP grade	IP54
Circumstance luminance	0-100,000Lux